i-SENSYS LBP6300dn
Specification Sheet

Printer Engine	
Print speed	30 ppm mono (A4)
Printing method	Monochrome laser beam printing
Print quality	Up to 2400 x 600 dpi with Automatic Image Refinement
Print resolution	Up to 600 x 600 dpi
Warm-up time	Approx. 10 seconds or less from power on
First Page Out Time	Approx. 6 seconds or less
Duty cycle	Max. 25,000 pages per month
Print margins	5 mm-top, bottom, left and right
Media handling	
Paper input (Standard)	250-sheet cassette 50-sheet multi-purpose tray
Paper input (Option)	500-sheet cassette
Paper output	150-sheet face down
Media types	Plain paper, Heavy Paper, Transparency, Label, Index card, Envelope
Media sizes	Cassette (Standard and optional): A4, B5, A5, A6, Legal, Letter, Executive, 16K,Custom sizes: Width 105 mm to 215.9 mm; Length 148.0 mm to 355.6 mm. Multi-purpose tray: A4, B5, A5, A6, Legal, Letter, Executive, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope Monarch, Index Card 76.2 mm x 127 mm, Custom sizes: Width 76.2 to 215.9 mm; Length 127.0 to 355.6mm.
Media weights	Cassette (Standard and optional): 60 to 120 g/m² Multi-purpose tray: 60 to 163 g/m²
Double sided printing	Automatic
General features	
Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1140 W or less Active: Approx. 570 W Standby: Approx. 9 W Typical Electricity Consumption (TEC): 2.03 kWh/week
Noise level	Sound power[1]: Active: 6.95 B or less Standby: 4.3 B or less Sound pressure[1]: Active: 53.5 dB(A) or less Standby: Inaudible
Dimensions (W x D x H)	400 mm x 376 mm x 260 mm
Weight	Approx. 11.8 kg
Operating environment	Temperature: 10 to 30ºC (50 to 86ºF) Humidity 20 to 80% RH (no condensation)
Control panel	5 LED indicators 1 Operation key
Controller	
Memory	16 MB
Printer languages	Canon Advanced Printing Technology (CAPT)
Interface and connectivity	USB 2.0 High-Speed, 10BASE-T/100BASE-TX
Software and printer management	NetSpot Device Installer, Remote User Interface (RUI)
Operating systems compatibility	Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7 Mac OS X Version 10.4.9-10.6[2] [3] Linux[2] [3]
Consumables	
All-in-One cartridges	Standard: Cartridge 719 (2,100 pages) High yield: Cartridge 719 H (6,400 pages)
Accessories/ options	
Items	PAPER FEEDER PF-44 (500-sheet cassette)

Standard disclaimer: All specifications subject to change without notice.

[1] Declared noise emission in accordance with ISO 9296
[2] Web distribution only
[3] English driver only
[4] Based on ISO/IEC 19752